



**IP 3130-2406 Product Specification**

Date: 2018-06-14

No: :FLKK0321806014

Customer		ENKOM	
Product Name		Factory Part No.	Customer Part No.
IP-PDU		IP 3130-2406	
Main Function		Description	
Monitor		Total load current for each phase	
		Input Voltage	
		Total power(kW) for each phase	
		Total energy consumption(kWh) for each phase	
		Temperature & Humidity state (1 T/H sensor port)	
Configure		Set the email alarm address	
		Set the threshold of total load current for each phase	
		Set HTTP	
		Set SNMP(v1)	
		Set network parameters(IP, gateway, subnet mask, DNS)	
Alarm	User defined alarm	Threshold of total current is exceeded for each phase	
	System default	When overload occurs	
	Alarm method	Buzzer beeping	
		Send E-mail to administrator automatically	
		SNMP sends trap alarm information	
	Central		Support central management of N units via CLEVER Manager software
User Management		Single user, user name and password configurable	
Access method		Web based, access via IP	
		SNMP v1	
		Telnet	
Daisy chain		Support daisy chain (Modbus version 1 master with max 31 pcs Slave, total are 32pcs PDU)	
Support remotely upgrade of software			
Software system		Support web browsers like IE, Firefox, and Google etc.	
Input/output			



Input	Rated input voltage		380V~ 50/60 Hz			
	Input terminal type		IEC60309 plug (16A 3P+N+E)			
	Cable specification		5×2.5mm ²			
	Cable length		3M			
	Rated current		3x16A			
	Overload protection		Optional			
Output	Outlet standard	IEC320 C13	Rated current	10A	Outlet quantity	24
	Outlet standard	IEC320 C19	Rated current	16A	Outlet quantity	6
	Rated output voltage		380VAC			
	Rated current		3x16A			
	Display		LCD, display input voltage, total current, total power(kW), energy consumption(kWh) and IP			
Physical characteristics	Dimension		L×W×H = 1494×50×44.4mm			
	Case material		Aluminum			
	Case color		Black			
Environment characteristics	Working environment		Temperature: 0-50° C, relative humidity 0-95%			
	Storage environment		Temperature:-10-60° C, relative humidity 0-95%			
Installation	Both sides brackets installation					
	Toll-less mounting (optional)					
Fittings	2pcs φ6×16mm cross bolt, 2pcs M6 float nut.					
<p>PDU drawing</p>  <p>IEC60309 plug (16A 3P+N+E)</p> 						
Design: Sabina		Customer confirm:	Check:	Authorized:		