



Prolab[®] Patch Panel Labels

The Prolab[®] PATCH ranges are made from durable polyester with a special laser print receptive surface. A strong acrylic adhesive ensures long term bonding.

Supplied in A4 sheets, print through an ordinary office laser printer. These labels are typically used for equipment/data outlets/patch panels etc.

TECHNICAL DATA

Printing method:	Standard Laser
Material:	Self-adhesive Polyester
Thickness:	50 micron
Sheet Size:	A4
RoHS:	Yes
Reach:	Yes

TESTING

Test	Method
Low Temperature	MIL-STD-810F Method 502.4 - 72 hrs @ -40°C
Elevated Temperature*	MIL-STD-202G Method 108A - 2000 hrs @ 70°C to 100°C
H2S Sour Gas	Exposure (2% H2S)
UV Weathering	ISO 4982 Part 3 Method A Cycle 1 - 3000 hrs
Salt Mist Spray	IEC60068-2-52 Test Kb Salt Mist (Cyclic)

*Samples were subjected to 500 hours @ 70°C, followed by 500 hours @ 85°C followed by 1000 hours @ 100°C



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1



Prolab[®] Patch Panel Labels

Additional Information

- Print using a standard office laser printer
- Pre-cut for rapid removal from sheet
- Fits a wide range of patch panels
- To print these labels, download our free Labacus[®] Innovator Basic labelling software

ORDER INFORMATION

Product Code	Label	Labels	Sheets		Colour
	Dims (mm)	Per Sheet	per Pack	Labels per pack	
PATCH 4L*	32 x 25	24	10	240	○
PATCH 6L*	10 x 20	75	10	400	○
PATCH 8L*	30 x 20	30	10	300	○

*Also available in packs of 100 eg PATCH 8L(100)

** Also available in  specify colour eg PATCH 8LW



STORAGE INSTRUCTIONS

Storage Instructions	Store between 50°F (10°C) and 77°F (25°C)
Conditions	Keep in dark conditions
Humidity Resistance	35% to 65% RH

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1