



Legend™ Thermal Tie-On Cable Labels

Made from a durable polyester, these labels are ideal for internal applications such as sub-stations and control rooms. (Also see Legend Laser range in A4 sheets)

Print via Fox-in-a-Box® thermal printer using "One One One" as for all our range of thermal labels using the Basic / Advanced / Professional.

How many labels can be printed from one ribbon?

A 300m thermal ribbon (full width) will yield approx. 16,00 labels.

TESTING

| Test | Method |
|------------------------|---|
| Elevated Temperature * | MIL-STD-202G Method 108A - 2000 hrs @ 70°C to 100°C |
| Low Temperature | MIL-STD-810F Method 502.4 - 72 hrs @ 40°C |
| H2S Sour Gas | Exposure (2% H2S) |
| Salt Mist Spray | EC60068-2-52 Test Kb Salt Mist (Cyclic) |

*Samples were subjected to 500 hrs @ 70°C, followed by 500 hrs @ 85°C, then 1000 hrs @ 100°C

TECHNICAL DATA

| | |
|------------------|---------------|
| Printing method: | DTP-1 Printer |
| Thermal Ribbon: | TSR3 |
| Material: | Polyester |
| Thickness: | 175 micron |
| RoHS: | Yes |
| Reach: | Yes |



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1



Legend™ Thermal Tie-On Cable Labels

Additional Information

FEATURES & BENEFITS

- Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm - unlimited
- Choice of two colours and six sizes

ORDER INFORMATION

| Product Code | Label Dims (mm) | Labels Per Roll | Rolls per Pack | Labels per pack | Colour |
|--------------|-----------------|-----------------|----------------|-----------------|--------|
| LM9013T | 90 x 13 | 3000 | 1 | 3000 | Yellow |



STORAGE INSTRUCTIONS

| | |
|----------------------|---|
| Storage Instructions | Store between 50°F (10°C) and 77°F (25°C) |
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0) 1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk

Copyright © Silver Fox | 2020 Version 1