Fox® Tie-On Cable Labels

TESTING

Resistance to Solvents

Elevated Temperature

Low Temperature

Test

A tough PVC tie-on cable label made from PVC. Ideal for commercial applications.

Print via Fox-in-a-Box® thermal printer using "**One One One"** as for all our range of thermal labels using the Basic / Advanced / Professional.

How many labels can be printed from one ribbon?

By way of example: LCP1-8015T (80mm x 15mm) will yield approx. 3,200 labels.

TECHNICAL DATA

| Printing method: | DTP-1 Printer |
|------------------|---------------|
| Thermal Ribbon: | TSR3 |
| Material: | PVC |
| Thickness: | 1mm |
| Colours: | White/Yellow |
| RoHS: | Yes |
| Reach: | Yes |



Method

MIL-STD-202-215 w/change 1

In House - 1000 hours @ 70C In House - 1000 hours @ -18C



Fox® Tie-On Cable Labels

Additional Information

ORDER INFORMATION

FEATURES & BENEFITS

- · Easy to use and apply
- Pre-perforated for rapid removal from roll
- Apply to any cable from OD Ø 10mm
 unlimited
- Choice of two colours and eight sizes

| | Label | Labels | Rolls | | |
|--------------|-----------|----------|----------|-----------------|-----------------------|
| Product Code | Dims (mm) | Per Roll | per Pack | Labels per pack | Colours |
| LCP1-6015T | 60 x 15 | 150 | 5 | 750 | \bigcirc |
| LCP1-8015T | 80 x 15 | 140 | 5 | 700 | \bigcirc \bigcirc |
| LCP1-10015T | 100x15 | 120 | 5 | 600 | \bigcirc \bigcirc |
| LCP1-12015T | 120x15 | 100 | 5 | 500 | \bigcirc |
| LCP1-6025T | 60x25 | 150 | 3 | 450 | $\bigcirc \bigcirc$ |
| LCP1-8025T | 80x25 | 140 | 3 | 420 | \bigcirc |
| LCP1-10025T | 100x25 | 120 | 3 | 360 | \bigcirc |
| LCP1-12025T | 120x25 | 100 | 3 | 300 | \bigcirc \bigcirc |
| | | | | | |



STORAGE INSTRUCTIONS

| Storage Instructions | Store between 50°F (10°C) and 77°F (25°C) |
|----------------------|---|
| Conditions | Keep in dark conditions |
| Humidity Resistance | 35% to 65% RH |

Disclaimer: The information contained in this datasheet is based on data we believe to be reliable and is given for information only and without guarantee and does not constitute a warranty. We are not able to anticipate every set of conditions, so always suggest that users should also satisfy themselves as to the suitability of our products for their particular environment and application and not make any assumptions based on information in this data sheet that is included or omitted. This datasheet supersedes any previous information/datasheet released and is subject to change without notice. E&OE.



For more information and to discuss your needs please contact our sales team on: +44 (0)1707 37 37 27 or email sales@silverfox.co.uk | www.silverfox.co.uk | support@silverfox.co.uk