



AVIAT ODU600 ETSI

The Aviat ODU 600 is the industry's first universal ODU with Flexible Power Mode (FPM) - providing software defined standard or high power modes of operation in a single platform. This unique scalability allows operators to pay for the power they need, when they need it, improving product lifecycle costs that cannot be achieved by using discrete fixed power mode ODUs. The ODU 600 balances both performance and cost optimization for public or private network operators deploying packet and/or TDM services to fixed, nomadic or mobile devices.



HIGHLIGHTS

- Industry's first universal ODU to support software defined standard(sp) and high power(hp) modes in a single ODU with Aviat's unique Flexible Power Mode (FPM) capability
- Highest transmit output power in its class of ODU across multiple frequency bands (6-38 GHz)
- Interoperates with the Eclipse ODU300 series to facilitate easy upgrade and evolution
- Compatible with the Eclipse IDU and INU transport and switching platforms
- Compact, power efficient design, supporting QPSK to 1024 QAM modulation
- Supports concurrent, ACM (Adaptive Coding & Modulation) & XPIC (Cross Pol. Interference Cancellation) operation
- Can be deployed in 1+0 unprotected, 1+1 MHSB (Monitored Hot Standby), 1+1 SD (Space Diversity) and 2+0 XPIC (Cross Pol. Interference Cancellation) configurations

PERFORMANCE & COST OPTIMIZATION USING FLEXIBLE POWER MODE

The Aviat ODU 600 is the first radio to be equipped with Flexible Power Mode (FPM) which delivers software-selectable standard or high power modes of operation in the same unit. This allows operators to optimize costs AND performance. With FPM, operators can deploy a standard power radio initially, and upgrade to high power (licensed-based) only when needed, thereby reducing initial CAPEX spending. The inherent economy of a single-box flexible power solution also helps streamline OPEX, with acute benefits for sparing and inventory management. The overall impact is a lower total cost of ownership.

The Aviat ODU 600 delivers best-in-class output transmit power across multiple frequencies, making it a highly attractive and competitive platform that builds on Aviat's ongoing radio innovation leadership. Increased power provides the flexibility to adjust for increased availability, throughput and/or distance. This performance translates directly into reduced antenna sizes, thereby driving down equipment capex and the opex contribution of tower leasing and maintenance.

KEY FEATURES

- Operating frequencies L6/U6, 7/8, 11, 13, 15, 18, 23, 26, 28, 32 and 38 GHz
- High throughput per T/R, per polarization:
 - Up to 454 Mbit/s data
 - Up to 100xE1 or 2xSTM-1
- Flexible Power Mode (FPM) for software defined standard power (sp) and high power (hp) modes in the same unit
- Transport options- Carrier Ethernet, PDH/SDH/SONET or Hybrid (mixed-mode Carrier Ethernet + PDH/SDH/SONET) in a single radio channel
- Full 256QAM Adaptive Coding and Modulation (ACM) - scalable up to 1024 QAM
- Configurations available: NP, MHSB, MHSB SD, 2+0 XPIC

SYSTEM PARAMETERS

GENERAL						
Frequency Band options						L6/U6, 7, 8, 11, 13, 15, 18, 23, 26, 28, 32, 38 GHz
Capacity Range	Airlink Capacity					8 - 366 Mbit/s
	Ethernet / IP Throughput					8 - 454 Mbit/s
	Native TDM					4 x E1 - 100 x E1 or 2 x STM-1
Modulation Options	Fixed/Adaptive					QPSK, 16, 32, 64, 128 and 256 QAM
Channel Sizes						7, 13.75 / 14, 27.5 / 28, 40 and 55 / 56 MHz
Configuration options						NP (1+0), Protected SB (1+1), Protected SB w/SD, XPIC
CONNECTORS						
IF Cable connector						N-Type
Antenna port Interface						Direct Antenna Mount
SYSTEM	L6/U6 GHZ	7/8 GHZ	11 GHZ	13 GHZ	15 GHZ	
Frequency Range, GHz	5.925 - 6.425 6.425 - 7.11	7.125 - 7.9 7.725 - 8.5	10.7 - 11.7	12.75 - 13.25	14.4 - 15.35	
T-R Spacings supported, MHz	252.04 340	150, 154, 161, 168, 175, 196, 245 119, 126, 151.614, 195, 208, 266, 300, 310, 311.32, 305.56, 360	490, 530	266	315, 420, 490, 640, 644, 728	
Maximum Tuning Range (dependent upon T-R spacing), MHz	56	56/140	165	84	245	
SYSTEM	18 GHZ	23 GHZ	26 GHZ	28 GHZ	32 GHZ	38 GHZ
Frequency Range, GHz	17.7 - 19.7	21.2 - 23.632	24.25 - 26.483	27.5 - 29.5	31.8 - 33.4	37.0 - 39.46
T-R Spacings supported, MHz	1010, 1092.5, 1120	1008, 1200, 1232	1008	1008	812	1260
Maximum Tuning Range (dependent upon T-R spacing), MHz	380	370	360	360	370	340
TRANSMITTER SPECIFICATIONS						
Manual Transmitter Power Control range						0 - 25 dB
Automatic Transmitter Power Control						Configurable over full available manual attenuation range
Transmitter Mute						> 50 dB
RECEIVER SPECIFICATIONS						
Frequency Stability						± 5 ppm
Receiver Overload/Max Receiver Input Level	BER=1x10 ⁻⁶ /BER=1x10 ⁻³					-15 dBm / 0 dBm
Residual (Background) Bit Error Rate						10 ⁻¹³
STANDARDS COMPLIANCE						
Operation						ETS 300-019 -class 4.1
Safety						IEC / EN 60950
RF Performance						EN 302 217 parts 1, 2.1 and 2.2
ENVIRONMENTAL						
Operating Temperature	Guaranteed					-33 to +55°C
	Extended					-50 to +65°C
Humidity	Guaranteed					100%
Altitude	Guaranteed					4500 Meters
ELECTRICAL AND MECHANICAL						
Power						< 40 Watts
Size						265 mm x 265 mm x 125 mm
Weight						5 kg

All specifications preliminary, and are typical values unless otherwise stated, and are subject to change without notice.

