



POCKET-SIZED



RUGGEDIZED

Introducing the JDSU Visual Fault Locators

with 2.5mm Interface
(1.25mm adapter available)

Whether installing or troubleshooting, the Visual Fault Locator (VFL) is an essential tool that quickly and easily locates problem areas in fiber cables. By pinpointing the exact location of fiber damage, technicians are able to diagnose, troubleshoot, and fix the problem efficiently. VFLs are also used for continuity tests and fiber identification.

JDSU offers two unique versions of VFLs that are economically priced and ergonomically designed for comfortable handling and portability. Both are equipped with a 2.5mm interface, compatible with connectors such as SC, ST, and FC, while the 1.25mm adapter enables connection to LC and MU connectors. The VFL emits a bright beam of red laser light (*Class II*), and as the light escapes from the damaged fiber, the illumination is easily visible from a distance. The *CONTINUOUS/FLASH* control button allows the option for continuous or flashing illumination.

FIBER TROUBLESHOOTING & VERIFICATION



Features

- Compact, ergonomic design for ultimate portability
- Visible wavelength = 650nm
- High powered laser (1 mW) for single-mode (> 7km) and multi-mode (> 5km) connectors
- Long-lasting battery life
- Continuous or Flash illumination
- Universal connector interface for quick & easy connection
- 2.5mm connector input
(1.25mm adapter available)
- Includes soft-sided carrying case with belt loop

Applications

- Locate sharp bends, breaks, and damages in fiber
- Perform end-to-end continuity tests
- Fiber tracing and identification

Visual Fault Locators

Pocket-sized & Ruggedized

COMPARISON

FFL-050 (Pocket-sized)

- Compact size for portability
- Uses 2 x "AAA" batteries *(included)* with 30+ hours continuous power
- Universal 1.25mm adapter sold separately

FFL-100 (Ruggedized)

- Rugged, shock-absorbing construction
- Uses 2 x "AA" batteries *(included)* with 80+ hours continuous power
- Professional-grade with Universal 1.25mm adapter included



Univ. 1.25mm Adapter

Benefits

- Easy-to-use; quickly & easily locate damage in optical fiber
- Economically priced
- Ruggedized and designed for demanding field use
- Continuous and Flashing illumination to locate damages quickly & easily
- Long-lasting battery life
- Protective rubber end cap

Specifications

	FFL-050 (Pocket-sized)	FFL-100 (Ruggedized)
Dimensions	11.4cm x 3.5cm x 2.0cm	22.0cm x 3.5cm x 3.0cm
Weight	46g with 2 AAA batteries	0.15g with 2 AA batteries
Fiber Compatibility	Single-mode, Multimode	Single-mode, Multimode
Wavelength	650nm (visible)	650nm (visible)
Laser Safety Rating	Class II	Class II
Output Power	1.0mW max	1.0mW max
Output Modes	Continuous and flashing	Continuous and flashing
Range	<ul style="list-style-type: none"> ▪ > 7km single-mode ▪ > 5km multimode 	<ul style="list-style-type: none"> ▪ > 7.5km single-mode ▪ > 5km multimode
Connector Interface	<ul style="list-style-type: none"> ▪ Universal 2.5mm (fixed) ▪ Universal 1.25mm adapter <i>(sold separately)</i> 	<ul style="list-style-type: none"> ▪ Universal 2.5mm (fixed) ▪ Universal 1.25mm adapter <i>(included)</i>
Controls	<ul style="list-style-type: none"> ▪ ON/OFF ▪ Continuous/Flashing 	<ul style="list-style-type: none"> ▪ ON/OFF ▪ Continuous/Flashing
Battery Type	2 x AAA	2 x AA
Battery Life	30+ hours on Continuous	80+ hours on Continuous
Carrying Case	Soft-sided w/ belt loop	Soft-sided w/ belt loop
Safety	1992, EN 61010-2, CE	1992, EN 61010-2, CE
Warranty	1 year	1 year



NORTH AMERICA
TEL: 1 866 228 3762
FAX: 1 301 353 9216

LATIN AMERICA
TEL: +55 11 5503 3800
FAX: +55 11 5505 1598

ASIA PACIFIC
TEL: +852 2892 0990
FAX: +852 2892 0770

EMEA
TEL: +49 7121 86 2222
FAX: +49 7181 86 1222

www.jdsu.com/inspect